



Technical Informations



Certificazione di qualità
UNI EN ISO 9001:2008

UNI EN ISO 14001:2004

Classic line

Code	066-0000000001
Name	"Z" welded locker
Dimensions (WxDxH)	1020x500x1800 mm
Inside Dimensions (WxDxH)	358/170x480x1140 mm
N° places	6
N° places for column	2
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	64
Volume (m3)	0,92



General informations

Base and corpus	Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended panel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels
Door	"Z" doors with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, upper and lower ventilation slots, transparent plastic label holder.
Lock	Cylinder lock type Yale with double key.
Closing	One way lever
Inside	Upper space with half shelf at h.500 mm. From the roof and bottom at h 1140 mm from the bottom , clothes hanger bar with plastic supports and hook . Left space with clothes hanger bar and roof at h 1140 from the bottom and right side h. 495 mm.
Colour door	Painting with epoxy powder color RAL 7035.
Colour corpus	Painting with epoxy powder color RAL 7035.
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

Possibilities

Base	On base, on inox feet, without feet.
Door	Without ventilation, with holes type 1, grid, HPL or plexiglass.
Lock	padlock handle, embedded padlock, mechanic combination , electronic combination and coin lock (€1,00).
Closing	–
Inside	Upper shelf , lower shelf .

Colour door

RAL-7035 light grey	RAL-1015 light ivory	RAL-1003 signal yellow	RAL-2004 pure orange	RAL-3001 signal red	RAL-5015 sky blue	RAL-5021 water blue	RAL-5012 light blue	RAL-3003 ruby red	RAL-6018 Yellow-green

Colour corpus



Technical Informations

SINCERT



Certificazione di qualità
UNI EN ISO 9001:2008

Code **066-0000000001**

Accessories.

Sloping roof
Support bench
2 sides for base
Frontal base
Kit "S" Hooks
Adjustable feet
Padlock
Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key
Padlock handle
"Z" upper door h. 1130mm, "Z" lower door h.1130 mm.

Certifications

UNI 9115/87 Erosion Taber
UNI 9428/89 Resistance to scratches
UNI 9429/89 Resistance to sudden changes in temperature
UNI 9300/88 e FA 276/89 Tendency to get dirty
UNI 9427/89 Resistance to light
UNI 9149/89 Mirror-like reflection
UNI EN ISO 9227/2006 Resistance to corrosion
UNI 8901/86 Resistance to slamming
UNI EN ISO 1520/95 Resistance trials
UNI 10782/1999 Hardness test- Pencil method
UNI EN ISO 2409/2007 Grid test

La presente scheda è proprietà esclusiva di San Polo Lamiere S.p.A. Div. Armet

Riproduzione vietata ai sensi di legge (art.171 Legge 22/04/1941 ,n.633).

L'utilizzo fraudolento ,senza regolare autorizzazione scritta anche se parziale e con qualsiasi mezzo, sarà tutelato a norma di Legge.

Il testo e quanto sopra specificato contengono informazioni riservate al destinatario indicato.

Il contenuto della presente e-mail confidenziale e la sua riservatezza è tutelata legalmente dal D.L.196/03.