

Base	On base, inox feet, without feet.	
door	Without ventilation, with grid, HPL or plexiglass.	
lock	padlock handle,embedded padlock,mechanic combination ,electronic combination and coin lock $({{f f}}.1,00).$	
closing		
Inside	upper and lower shelf	
door color		
corpus color	Ral-7035 RAL-1015 RAL-1003 RAL-2004 signal yellow RAL-3001 RAL-5015 RAL-5012 RAL-5012 RAL-3003 RAL-6018 Yellow	
coi pus coi0i		

RAL-5021

water blu

RAL-5012

light blue

RAL-3003

ruby red

RAL-100

Bal-7035

light grey

RAL-1015

light ivo

RAL-200

RAL-3001

signal red

BAL-5015

sky blue

RAL-6018

Yell

S. POLO LAMIERE S.p.A. divisione ARMET Via Cisa Ligure, 43-42041 BRESCELLO (RE) ITALIA Tel. +39.0522.686009–Fax+39.0522.686015-info@armet.it-www.armet.it

Technical informations





leg. n° 8231-E ISO 14001

	262-0000000001	n° 50 100 2898
Accessories.		
Sloping roof		
Support bench		
2 sides for base		
Frontal base		
Kit "S"hooks		
Adjustable feet		
Padlock		
Anti-corrosion cov	ver for feet	
Spare parts		
Cylinder lock type	Yale with double key	
Padlock handle		
"Z" upper door h.	1130mm, "Z" lower door h.1130 mm.	
Certifications		
UNI 9115/87 Erosio	on Taber	
UNI 9428/89 Resist	tance to scratches	
UNI 9429/89 Resist	tance tosudden changes in temparature	
UNI 9300/88 e FA 2	276/89 Tendency to get dirty	
UNI 9427/89 Resist	tance to light	
UNI 9149/89 Mirro	or-like reflection	
UNI EN ISO 9227/2	2006 Resistance to corrosion	
UNI 8901/86 Resist	tance to slamming	
UNI EN ISO 1520/9	95 Resistance trials	
UNI 10782/1999 H	ardness test- Pencil method	
	2007 Grid test	

These data are exclusive property of San Polo Lamiere S.p.A. Div. Armet

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.