



# Technical informations



Certificato Sistema di Gestione Qualità n° 50 100 2898

Reg. n° 8231-E ISO 14001

## Quadro Line

Code	<b>264-0000000001</b>
Name	"Z" monobloc locker
Dimensions (WxDxH)	810x500x1800 mm
Inside Dimensions (WxDxH)	418/210x480x1140 mm
N° places	4
N° places for column	2
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	45
Volume (m3)	0,72



### General Informations

Base and corpus	Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended pannel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels
Door	Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, squared holes for ventilation ,squared handle with label holder.
Lock	Cylinder lock typo Yale with double key.
Closing	One way lever
Inside	Upper dorr with upper half shelf and h.500 mm. from the roof bottom ta h 1140 mm from the bottom , steel clothes hanger bar with plastic support with hook .Left door with clothes hanger bar roof at h 1140 drom the bottom and right side h. 495 mm.
Colour door	Painting with epoxy powder color RAL 7035.
Colour corpus	Painting with epoxy powder color RAL 7035.
Law	In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

### Possibilities

Base	On base, inox feet, without feet.
door	Without ventilation, with grid, HPL or plexiglass.
lock	padlock handle, embedded padlock, mechanic combination ,electronic combination and coin lock (€1,00).
closing	–
Inside	upper and lower shelf

door color

RAL-7035 light grey	RAL-1015 light ivory	RAL-1003 signal yellow	RAL-2004 pure orange	RAL-3001 signal red	RAL-5015 sky blue	RAL-5021 water blue	RAL-5012 light blue	RAL-3003 ruby red	RAL-6018 Yellow green

corpus color

RAL-7035 light grey	RAL-1015 light ivory	RAL-1003 signal yellow	RAL-2004 pure orange	RAL-3001 signal red	RAL-5015 sky blue	RAL-5021 water blue	RAL-5012 light blue	RAL-3003 ruby red	RAL-6018 Yellow green



## Technical informations



Certificato Sistema di  
Gestione Qualità  
n° 50 100 2898



Reg. n° 8231-E  
ISO 14001

Code **264-0000000001**

### Accessories.

Sloping roof

Support bench

2 sides for base

Frontal base

Kit "S"hooks

Adjustable feet

Padlock

Anti-corrosion cover for feet

### Spare parts

Cylinder lock type Yale with double key

Padlock handle

"Z" upper door h. 1130mm, "Z" lower door h.1130 mm.

### Certifications

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance to sudden changes in temperature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test